

TATUNG V42MAGI

Peerless digital pedigree... The Tatung 42" PAL/DVB-T hybrid SoC packed iDTV

Features

- Integrated PAL/DVB-T hybrid system into one chip
- Compatible with all 576i/576p/720p/1080i video formats
- Progressive Scan, 2:2 Pull Down
- Digital 3D Comb Filter, 3D De-interlacer
- CAM (Common Access Module, CI) available for CA to Pay-TV
- MHEG-5 ready for UK to Interactive Service from CA
- Pass Nordic Basic TV Profile & support "Digital Teletext" (Germany)
- OAD (Over Air Download) for DVB-T software upgrade
- Provided 7 days EPG, Canal+, APS, AVC

System Spec.

- Resolution: 1366 x 768
- Contrast Ratio: 1200:1
- Response Time: 8 ms
- Brightness: 500 cd/m2
- HDMI/DVI Connectivity



Items	Model Name	V42MAGI (EU Model)	
Panel	Resolution	1366 x 768 (16 : 9)	
	Contrast Ratio	1200 : 1 (typ.)	
	Brightness (center)	500 cd / m2 (typ.)	
	Viewing Angle (CR>10)	178° Hor. / 178° Ver. (typ.)	
	Response Time (BTW)	8ms(typ.)	
TV function	Broadcasting System	Analog : PAL / SECAM	Digital : DVB-T
	Receiving Channel	Analog : B / G, D / K, I and L / L'	Digital : 54MHz ~ 864MHz
	Sound System	Analog : NICAM / A2 (IGR)	Digital : PCM
	Data Broadcasting	Teletext 100 pages (FLOF / TOP) , Auto Program Searching (APS)	
Video Input	Video Color System	PAL / SECAM / NTSC	
	AV1 (SCART)	21-pin Scart (RGB / CVBS)	x 1
	AV2 (SCART)	21-pin Scart (RGB / CVBS/ SVHS)	x 1
	AV3 (CVBS, Y/C)	Composite (RCA jack)	x 1
	AV4 (Component)	S-Video	x 1
	AV5 (HDMI)	Y Pb Pr (720p / 1080i , HDTV ready)	x 1
PC Input (analog)	HDMI 19 pin	x 1	(HDMI 1.1 / HDCP 1.1)
	DVI-D Connection	DVI-D	x 1
Audio Input	VGA Connection	D-Sub 15 pin	x 1
	Audio 1	SCART (build-in)	x 2
Audio Input	Audio 2	Composite	x 1
		S - Video	x 1
		Component	x1
	Audio 3	PC	x 1
Video Output	SCART 1	TV / CVBS / S-Video/DTV	
	SCART 2	TV / CVBS / S-Video/DTV	
	Composite (RCA jack)	TV / CVBS/SCART1/SCART2/DTV	
Audio Out	Speaker (build-in)	15W + 15W (rms) @ THD < 10%	
	Without Accessories	Left / Right / Subwoofer	
	SP/DIF	All source except VGA and DVI	
Feature	OSD Language	English, French, German, Spanish, Italian, Finnish, Swedish, Danish, Demark, Norwegian	
	Function Keys	Power , Source , Menu , Up/Down(Channel) , +/- (Volume) , ARC/EXIT .	
	Video Performance	3D Comb-filter , 3D De-interlace, Advanced Chroma Processing, Video Enhance, Noise Reduction, 2-2 Pull Down	
	Audio Performance	Equalizer, Subwoofer, Auto Volume Control (AVC),	
	Other Control	PIP, Canal+, Auto Progress System (APS), Aspect Ratio Control (ARC), Auto Picture Control (APC), Auto Sleep Timer, Auto Power On	
Power	Power supply	AC 100V ~ 240V , 50 / 60Hz	
	Power Consumption	260 W	
Dimensions	W x H x D	1111.3mm x 632.3mm x 279.7mm	
Weight (Net)	Without Accessories	31.0 kg	

DVB-T Software Minimum Spec & Features

Channel Scan	<input checked="" type="checkbox"/>	7 Days EPG	<input checked="" type="checkbox"/>
Channcce Edit	<input checked="" type="checkbox"/>	Digital Teletext (Germany)	<input checked="" type="checkbox"/>
Program Now	<input checked="" type="checkbox"/>	MHEG-5 (Only To UK)	<input checked="" type="checkbox"/>
Program Next	<input checked="" type="checkbox"/>	Common Interface (PCMCIA)	<input checked="" type="checkbox"/>
DVB Subtitling	<input checked="" type="checkbox"/>	OverAir DVB-T Software Upgrade	<input checked="" type="checkbox"/>

**Product specification and design are subject to change without notice.